

**ESTE ELECTRIC HEAT FEATURES:**

- Primary over temperature protection provided by auto reset thermal cutout – disc type
- Air proving switch (requires min Pt total pressure of .07" w.g. at the face of the electric coil)
- De-rated Nickel Chrome heating elements
- 24V Class 2 control transformer (inherently limiting)
- Magnetic / safety contactors as required (UL listed for minimum of 250,000 cycles)
- Line and control terminal blocks
- Up to 3 steps of heat
- ETL listed assembly

**ESTE OPTIONAL FEATURES:**

- Door-interlocking disconnect switch (non-fused)
- Main power fuses (fuses and fuse blocks)
- Mercury contactors
- Proportional SSR control (0-100%)
- Discharge temperature limiting control
- Secondary over temperature protection with manual reset (push button) thermal cutout – disc type

**Table 44: Electric Heating Coil Performance - Allowable KW**

Size	Fan CFM	# Steps	1 - Phase						3 - Phase			
			120 V KW Range		240 V KW Range		277 V KW Range		208 V KW Range		480 V KW Range	
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
33	1100	1	0.5	5.0	0.5	10.9	0.5	12.5	0.5	15.0	1.0	15.7
		2	1.0		1.0		1.0		1.0			
		3	1.5		1.5		1.5		1.5			
50	1600	1	0.5	4.5	0.5	10.5	0.5	12.0	0.5	14.0	1.0	20.0
		2	1.0		1.0		1.0		1.0			
		3	1.5		1.5		1.5		1.5			
75	2000	1	0.5	4.0	0.5	10.0	0.5	11.5	0.5	12.5	1.0	28.6
		2	1.0		1.0		1.0		1.0			
		3	1.5		1.5		1.5		1.5			
10	2400	1	0.5	4.0	0.5	10.0	0.5	11.5	0.5	12.5	1.0	34.3
		2	1.0		1.0		1.0		1.0			
		3	1.5		1.5		1.5		1.5			
Fan Nameplate Voltage			120 V		240 V		277 V		120 V		277 V	

**Notes:**

1. The Max Allowable KW shown is based on UL / NEC standards, in conjunction with laboratory tests of ESTE air terminal assemblies.
2. The minimum air flow requirement for terminals with electric coils is the greater of 70 cfm/KW or the minimum allowable flow rate that can be accurately controlled. This allows proper operation of the electric coil and results in increased coil life with a maximum air temperature rise of 45° F to prevent thermal stratification in the space. Refer to table 33, page D-30 to determine minimum and maximum flow rates for the control system selected.
3. Uniform flow through a coil results in optimum performance, and therefore, we recommend a minimum length of 48" of full size discharge duct after the air terminal.