

Static Pressure Drop

| Inlet Size | Airflow (CFM) | Pressure Drop (IN WG) XEZTS & XEZTA |
|------------|---------------|-------------------------------------|
| 5 | 125 | 0.08 |
| | 175 | 0.15 |
| | 250 | 0.32 |
| | 300 | 0.46 |
| | 350 | 0.62 |
| 6 | 200 | 0.09 |
| | 250 | 0.14 |
| | 300 | 0.19 |
| | 350 | 0.27 |
| | 400 | 0.35 |
| 7 | 250 | 0.07 |
| | 300 | 0.10 |
| | 400 | 0.17 |
| | 500 | 0.27 |
| | 600 | 0.38 |
| 8 | 350 | 0.08 |
| | 475 | 0.14 |
| | 600 | 0.22 |
| | 700 | 0.31 |
| | 900 | 0.51 |
| 9 | 450 | 0.08 |
| | 525 | 0.11 |
| | 600 | 0.14 |
| | 700 | 0.19 |
| | 900 | 0.32 |
| | 1100 | 0.47 |

| Inlet Size | Airflow (CFM) | Pressure Drop (IN WG) XEZTS & XEZTA |
|------------|---------------|-------------------------------------|
| 10 | 550 | 0.08 |
| | 675 | 0.12 |
| | 800 | 0.16 |
| | 1000 | 0.26 |
| | 1200 | 0.37 |
| | 1400 | 0.50 |
| 12 | 800 | 0.08 |
| | 1000 | 0.12 |
| | 1200 | 0.18 |
| | 1400 | 0.24 |
| | 1700 | 0.36 |
| | 2000 | 0.49 |
| 14 | 1050 | 0.07 |
| | 1400 | 0.13 |
| | 1800 | 0.22 |
| | 2200 | 0.32 |
| | 2600 | 0.45 |
| | 3000 | 0.60 |
| 16 | 1400 | 0.08 |
| | 1900 | 0.14 |
| | 2400 | 0.22 |
| | 2900 | 0.33 |
| | 3500 | 0.48 |
| | 4100 | 0.66 |

Notes:

1. Air pressure drop is the difference in static pressure from the terminal inlet and discharge with the damper in the fully open position.